

PIPE SURFACE PROBE (CLAMP-TYPE) Sheath - stainless steel 1.4541. Cable - SLSL (silicone insulated)	T (TST)	SENSITIVE ELEMENT	TEMPERATURE RANGE	DIMENSIONS		
				n[mm]	d[mm]	wires
<p>$k = 50 \dots 10\,000 \text{ mm}$ $D = 50 \dots 1\,000 \text{ mm}$</p>		1 x Pt (RB,RD,RF,RG)	T9 -50...200 °C	30...50	5, 6	2, 3, 4*
		1 x Cu (RH, RK)	T9 -50...200 °C	50	5, 6	2, 3, 4*
		1 x J, 1 x K	T7 0...200 °C	30...50	5, 6	2
		1 x T	T7 0...200 °C	30...50	5, 6	2
* Please, contact COMECO!						

TS

ANGLED PIPE-SURFACE PROBE Sheath - stainless steel 1.4541. Cable - SLSL (silicone insulated)	TL (TSTL)	SENSITIVE ELEMENT	TEMPERATURE RANGE	DIMENSIONS		
				n[mm]	d[mm]	wires
<p>$k = 50 \dots 10\,000 \text{ mm}$ $D = 50 \dots 1\,000 \text{ mm}$</p>		1 x Pt (RB,RD,RF,RG)	T9 -50...200 °C T1** -50...400 °C	30...50	5, 6	2, 3, 4*
		1 x Cu (RH, RK)	T9 -50...200 °C	50	5, 6	2, 3, 4*
		1 x J, 1 x K	T7 0...200 °C T8** 0...400 °C	30...50	5, 6	2
		1 x T	T7 0...200 °C	30...50	5, 6	2
* Please, contact COMECO! ** With GLGLP cable (not moisture-proof). Contact COMECO!						

TOROIDAL PROBE Sheath - stainless steel 1.4541. Cable** - GLGLP (glass fibre with steel braid)	TO (TSTO)	SENSITIVE ELEMENT	TEMPERATURE RANGE	DIMENSIONS		
				n[mm]	d[mm]	wires
<p>$D = 10 \dots 30 \text{ mm}$ $k = 50 \dots 10\,000 \text{ mm}$</p> <p>** With silicone cable - TOE</p>		1 x Pt (RB,RD,RF,RG)	TO: T7 0..200 °C	15	5, 6	2, 3*, 4*
			TOE: T9 -50..200 °C	15	5, 6	2, 3, 4*
		1 x Cu (RH, RK)	TO: T7 0..200 °C	50	5, 6	2, 3*, 4*
			TOE: T9 -50..200 °C	50	5, 6	2, 3, 4*
		1 x J, 1 x K	TO: T8 0...400 °C	15	5, 6	2
			TOE: T7 0...200 °C	15	5, 6	2
		1 x T (only for TOE)	TOE: T7 0...200 °C	15	5, 6	2
	* Please, contact COMECO!					

COMECO reserves the right of changing specifications without prior notice!